

# Hydrogen Supply Cabinet 20MPa – SS002

## Fast hydrogen trailer unloading for H2Station®

- Flexible 20MPa connection interface for any delivery trailer type.
- Automatic unloading sequence optimized for fast and full transfer.
- Safe use and activation of unloading via HMI screen interface.
- Safety interlocks ensure correct connection with delivery trailer.
- Flexible placement at site up to 100 meters from Supply Storage (SS001).


### Specifications

---

<b>Operating pressure:</b>	Nominal: 20MPa   Maximum: 24MPa
<b>Unloading process:</b>	Automatic – optimized for fast and full transfer
<b>Trailer connection interface:</b>	Standard: DIN 417-1 connection   Optional: flexible connection type depending on specific delivery trailer
<b>User interface:</b>	HMI screen for activation of unloading sequence
<b>Dimensions – Supply Cabinet:</b>	L: 762mm W: 600mm H: 1755mm
<b>Dimensions – Activation HMI:</b>	L: 503mm W: 300mm H: 1744mm
<b>Weather resistance:</b>	Stainless steel enclosure for outdoor installation
<b>Visual appearance:</b>	Optional graphical foil with customer branding
<b>Operating temperature:</b>	-20°C to 40°C
<b>Placement at site:</b>	Up to 100 meters from Supply Storage (SS001)
<b>Installation platform:</b>	Underground pit box for pipe and wire connections
<b>Scope and interface:</b>	Turnkey module ready for connection with Hydrogen Supply Storage (SS001).
<b>Safety equipment:</b>	Mechanical and Safety Instrumented System IEC61511
<b>Approvals &amp; certifications:</b>	– CE marked – PED (2014/68/EU) Notified body Bureau Veritas



Hydrogen Supply Cabinet



Activation HMI