



S Series

Hydrogen Generation Systems



MODEL	S10	S20	S40
Description	On-site hydrogen generator in an integrated, automated, site-ready enclosure Load following operation automatically adjusts output to match demand Full differential Pressure, H ₂ over O ₂		
Electrolyte	Proton Exchange Membrane (PEM) – Caustic-Free		
HYDROGEN PRODUCTION			
Nominal Production Rate Nm ³ /h @ 0°C, 1 bar SCF/h @ 70°F, 1 atm SLPM @ 70°F, 1 atm kg/24 h	0.27 Nm ³ /h 10 SCF/h 4.8 SLPM 0.58 kg/24 h	0.53 Nm ³ /h 20 SCF/h 9.4 SLPM 1.14 kg/24 h	1.05 Nm ³ /h 40 SCF/h 18.8 SLPM 2.27 kg/24 h
Delivery Pressure – Nominal	13.8 barg (200 psig)		
Power Consumption by System per Volume of H ₂ Gas Produced ¹	6.1 kWh/Nm ³ (16.3 kWh/100 ft ³)		
Purity (Concentration of Impurities)	99.9995% [H ₂ O < 5 ppm, -65°C (-85°F) Dew Point, N ₂ < 2 ppm, O ₂ < 1 ppm, all other undetectable]		
Turndown Range	0-100% net product delivery (automatic)		
Upgradeability	N/A		
DI WATER REQUIREMENT			
Consumption Rate at Maximum Production	0.26 L/h (0.08 gal/h)	0.47 L/h (0.13 gal/h)	0.94 L/h (0.25 gal/h)
Temperature	5-35°C (41-95°F)		
Pressure	1.5-4 barg (21.8-58 psig)		
Input Water Quality	Required: ASTM Type II Deionized Water, < 1µS/cm (> 1 MΩ-cm) Preferred: ASTM Type I Deionized Water, < 0.1 µS/cm (> 10 MΩ-cm)		
HEAT LOAD AND COOLANT REQUIREMENT			
Coolant	Air-cooled; ambient air		
Maximum Heat Load	1.1 kW (3,754 BTU/h)	2.2 kW (7,507 BTU/h)	4.3 kW (14,673 BTU/h)
ELECTRICAL SPECIFICATIONS			
Maximum Power Required within Expected System Life	3 kVA	4.5 kVA	8.5 kVA
Electrical Requirements	208-240 VAC, single phase, 50 or 60 Hz		

Model	S10	S20	S40
INTERFACE CONNECTIONS – CONSULT INSTALLATION MANUAL FOR DETAILS			
H ₂ Product Port	1/4" CPI™ compression tube fitting, SS		
H ₂ /H ₂ O Vent Port	1/2" CPI™ compression tube fitting, SS		
O ₂ Vent Port	3/8" FNPT		
DI Water Port	1/4" tube push-to-lock, polypropylene		
Drain Port	1/4" tube push-to-lock polypropylene		
Electrical	Connect to on-board circuit breaker		
Communications	Ethernet, 24 VDC dry contacts		
CONTROL SYSTEMS			
Standard Features	<ul style="list-style-type: none"> Fully automated, push button start/stop Automatic fault detection and system depressurization 		<ul style="list-style-type: none"> E-stop Remote start/stop On-board H₂ leak detection Remote communications
Remote Shutdown	Hardwire input to safety PLC		
PHYSICAL CHARACTERISTICS			
Dimensions W x D x H	Product Est. Shipping	79 cm x 97 cm x 112 cm (31" x 38" x 44") 97 cm x 114 cm x 137 cm (38" x 45" x 54")	
Weight	Product Est. Shipping	209 kg (460 lbs) 289 kg (635 lbs)	
IP Rating	IP 22		
ENVIRONMENTAL CONSIDERATIONS – DO NOT FREEZE			
Standard Siting Location	Indoor, level ± 1°, 0-90% RH non-condensing, non-hazardous/non-classified environment		
Storage/Transport Temperature	5-60°C (41-140°F)		
Ambient Temperature Range	5-40°C (41-104°F); Optional: 5-50°C (41-122°F)	5-40°C (41-104°F)	
Altitude Range – Sea Level	1,520 m (5,000 ft)		
Ventilation	Proper ventilation must be provided from a non-hazardous area, at a rate in accordance with IEC60079-10, Zone 2 NE		
SAFETY AND REGULATORY CONFORMITY			
Maximum On-board H ₂ Inventory at Full Production	0.016 Nm ³ 0.56 SCF 0.001 kg		
Cabinet Ventilation with Environment	NFPA 69 and EN 1127-1, Clause 6.2 Vent fan draws fresh air up to 28 Nm ³ /min (1,000 ft ³ /min)		
Noise dB(A) at 1 Meter	< 70		
Conformity	cTUVus (UL and CSA equivalent), CE (PED, Mach. Dir., EMC), ISO 22734-1		




Specifications are subject to change. Please contact Nel Hydrogen for solutions to best fit your needs.

¹ Dependent on configuration and operating conditions.

www.nelhydrogen.com | +1.203.949.8697 | info@nelhydrogen.com

MADE IN USA

© 2019 Nel ASA. All Rights Reserved. Nel, number one by nature, Proton, and the Nel and Proton logos are trademarks of Nel ASA or its subsidiaries.



PD-0600-0061 Rev F